

Fact sheet

Sound emitter TYFONIC® Delta 2



Modern design, compact and powerful

The electronic siren TYFON® Delta range is characterized by its modern and unique design and excellent sound quality. The modular models are suitable for all environments and adjust to harsh external conditions. The sirens are perfectly suitable for urban areas with a high level of background noise, for wide area sound coverage as well as for industrial facilities. The sound propagation from the unique folded horn guarantees almost perfect all-round acoustics. Through the distinctive shape of the sound emitter and the high-quality components, an excellent acoustic efficiency can be reached.

Article number

- Art. no. with 3" mast foot 255.30.099

CE label

- EMV: guideline/directive 2014/30/EU
- LVD: guideline/directive 2014/35/EU
- METAS test report no. 259-15527
- FOCF authorisation no. BZS AL 17-801

Acoustic characteristics

nominal value

- Sound pressure level at 380 Hz @ 1 m 136 dB(A)
- Sound pressure level at 380 Hz @ 30 m 106 dB(A)
- Range of 65 dB at 380 Hz 700 m
- village-like building development (S1)

Electrical properties

- Compression elements 2
- Power input 2 x 125 W

Material properties and climatic characteristics

- Material, sound emitter Aluminium
- Material, mast foot Galv. steel
- Guaranteed wind load tolerance 180 km/h
- Temperature resistance -20°C - +60°C
- Protection class IP 54

Dimension and weight

Nennwert

- Height 825 mm
- Weight 23 kg



Kockum Sonics AG | Oberdorfstrasse 64 | PO Box | CH-8600 Dübendorf
info@kockumsonics.ch | Tel. 044 820 31 91 | www.kockumsonics-ag.ch



Masse in mm.

