

Fact sheet ET500 mobil



Kockum Sonics – We are experts in the field of large-scale alert and warning systems since 1961.

Loudspeaker ET500 mobil

• Art. no. loudspeaker ET500 mobil	AT-1037
• Material	Aluminium
• Sound pressure level 380 Hz, 1 m	122.0 dB(A)
• Compression elements	2
• Power input	2x 250W
• Temperature range	-30° - +60°
• Height with warning light	600mm
• Height without warning light	420mm
• Weight	18 Kg with roof rack
• Protection class	IP 54

Amplifier TK 150 MkIIS

• Art. no. amplifier TK150 MKS II	A-1521
• Material casing	Aluminium black
• Temperature range	-20° - +60°
• Operating voltage	12 - 14 V DC
• Power consumption	170 W
• Output power loudspeaker	1x 100W (370 Hz)
• Memories 1 + 2	2x 160 seconds
• Weight incl. microphone	2.5 kg
• Dimensions (WxHxD) with handle	156 x 68 x 220 mm

Interfaces

• Microphone	DIN 5-pole, 270°
• Line-in connector	3.5mm jack plug
• Loudspeaker (and warn light)	DIN 41 622, RP 622,
8-pole coupling	
• Power supply	DIN 41 622, RP 622,
8-pole plug	
• Data communication	USB (Typ B)